Coda System Administration

Peter J. Braam and Henry M. Pierce v1.1, Nov 9, 1997

This document describes the current implementation of the Coda system administration, it's problems and ideas for future design.

Contents

1 Introduction **2**

1.1 bldvldb.sh 2

1 Introduction

- Volume databases (text)
- `/vice/vol/VolumeList` Holds partition and volume information for volumes for which this server is custodian. This is file is generated by srv.
- `/vice/vol/groupid` is maximum replicated volume id allocated so far.
- HOSTS (text)
  - Entries describe volume storage groups: id hostname1 hostname2 etc. Stored in /vice/db/VSGDB
  - `/vice/db/hosts` servers should be in this file. Servers found in the VSGDB are checked to be in this file before proceeding to make a volume.
  - `/vice/db/servers` contains an id for each server.

Createvol_rep works as follows: Parameters are: <volname> <vsgaddr> <partitionname> [<groupid>]

- check we are the SCM
- Check that the volname doesn't appear in AllVolumes or VRList
- Get the list of servers from the vsgaddr using the VSGDB
- verify the servers against /vice/db/hosts
- get a new replicated id for this replicated volume using the `/vice/vol/groupid` file
- use volutil to create the volume on each host, using the partition, volumename and groupid acquired before. Note that each server now assigns a volume id for this newly created volume. It dumps

1.1 bldvldb.sh

- get `/vice/vol/VolumeList` from each server in `/vice/db/hosts`. Names is server-name.list.new. First try this using ftp, then rfs, then krcp.
- if the file was acquired move it to `/vice/vol/remote/server-name.list`
- dump them all in `/vice/vol/BigVolumeList`
- volutil rebuilds the VLDB with `volutil makevldb /vice/vol/BigVolumeList`

Note this rebuilds the VLDB on the machine where is script is run, i.e. the scm.